



ELECTRIC CLUTCH ENGAGEMENT. A simple flip of a switch engages the clutch, eliminating a need for manual manipulation of a belt tensioner or engine slide adjustment.



PATENTED YELLOW JACKET™ **CUTTER SYSTEM.** The Vermeer-exclusive Yellow Jacket cutter system is designed to provide faster, easier serviceability, as well as extended pocket and tooth life.



DRIVE SYSTEM. The SC372 features a belt-driven gearbox drive system which provides an efficient transfer of horsepower from the engine to the cutter wheel.



OPERATOR PRESENCE SYSTEM. The SC372 is equipped with three operator-sensing control levers that monitor the operator's touch and maintain cutter wheel engagement. When the operator's hands leave the control levers, an automatic disengage and braking sequence will stop the cutter wheel in less than nine seconds. With this safety system, the cutter wheel will automatically stop when the operator releases the hydraulic cutter wheel controls.



OPTIONAL CHIP BLADE. The blade which is hydraulically controlled from the operator's station, helps eliminate the need for manual chip raking during jobsite cleanup.



EXTENDED WARRANTY. The 3-year/3000-hour extended limited warranty on applicable stump cutter belt-drive system offers you peace of mind, in addition to the 1-year/1,000-hour Vermeer equipment limited warranty.











🛂 🛗 💟 💌 VERMEER.COM



SC372 STUMP CUTTER

GENERAL

Weight (diesel engine): 2270 lb (1029.7 kg) Weight (gas engine): 1860 lb (843.7 kg)

Length: 10.3' (3.3 m)

Width (without duals): 34.8" (88.4 cm)
Width (with duals): 49.5" (125.7 cm)
Height (diesel engine): 55.4" (140.7 cm)
Height (gas engine): 59" (149.9 cm)

ENGINE OPTIONS

Make and model: Yanmar 3TNV88-BDVR - Diesel

Gross horsepower: 37.8 hp (28.2 kW) **Max torque:** 79.5 ft-lb (107.8 Nm)

Electrical system: 12 V

Fuel-tank capacity: 9 gal (34.1 L)

Make and model: Briggs & Stratton Vanguard - Gas

Gross horsepower: 35 hp (26.1 kW) Max torque: 53 ft-lb (71.9 Nm)

Electrical system: 12 V

Fuel-tank capacity: 9 gal (34.1 L)

HYDRAULIC SYSTEM

Oil-tank capacity: 6 gal (22.7 L)

Oil type: VMF

CUTTER WHEEL DRIVE

Wheel diameter (without teeth): 18" (45.7 cm)

Wheel thickness: .5" (1.3 cm)

Drive: Two-stage, Vee-belt and gearbox
Tooth style: Yellow Jacket cutter system

Tooth quantity: 24

CUTTING DIMENSIONS

Above ground level: 21" (53.2 cm)

Below ground level: 16" (40.6 cm)

Width (straight line): 40" (101.6 cm)

OPTIONAL

AutoSweep Chip blade

Four-wheel drive

NOTES:		

