



TROMMEL SCREEN LINE





Get more out of your daily grind with Vermeer

Whether you're just entering the composting market or are experienced and looking to grow your operation, Vermeer, with its recent acquisition of Wildcat Mfg. Co., Incorporated, makes it easier to capitalize on the market opportunities. We offer rugged, reliable equipment that can help you quickly and efficiently process organic waste into quality end product.

Our trommel screens ensure that ground material is screened and separated thoroughly, then placed where you need it. They are designed to minimize setup time, and with an extensive list of options, they can be manufactured to fit your specific needs.

Additionally, Vermeer horizontal and tub grinders offer outstanding grinding performance and innovative features that optimize efficiency and safety. Our elevating-face and drum-style compost turners maximize windrow aeration, helping speed decomposition, thereby increasing facility productivity.

All of our organic waste recycling equipment is backed by the dedicated support of your local Vermeer dealer, providing training, parts and service every step of the way.

TR510

The TR510 by Wildcat is a self-contained, portable screening plant designed for the organic and wood-waste industries and is ideal for composting, recycling or topsoil reclamation. With its 49-hp (36.5 kW) engine, 5' diameter (1.5 m) drum and 5 cu yd (3.8 m³) hopper, the TR510 can produce up to 65 cu yd (49.7 m³) of consistent, quality material per hour with minimal spillage.

The hopper is not only one of the largest in its class, but its low infeed height decreases loading cycles and eliminates the need for loading ramps with most loaders. The hopper's steep sidewalls and large throat opening helps keep material from bridging.

TR510 Specifications

General Dimensions

Weight: 23,000 lb (10,433.6 kg)
 Hitch weight: 5700 lb (2585.5 kg)
 (weights will vary with options)
 Length (transport): 29.3' (8.9 m)
 Width (transport): 92" (233.7 cm)
 Height (transport): 13.4' (4.1 m)
 Length (operational): 50' (15.2 m)
 Width (operational): 92" (233.7 cm)
 Height (operational): 11.3' (3.4 m)

Capacity

65 cu yd (49.7 m³) per hr with .5" (1.3 cm) screens
 installed and material with moisture less than 40%

Engine

Make and model: John Deere PE 4024T Tier 3
 Cylinders: 4
 Engine rating: 49 hp (36.5 kW) @ 2800 rpm 129 ft-lb
 (174.9 Nm) of torque @ 1500 rpm
 Fuel consumption: 2.4 gph (9.1 L/h) under most
 operating conditions

Hopper and Apron Conveyor

Hopper capacity: 5 cu yd (3.8 m³)
 Hopper height: 6.8' (2.1 m) from ground level at
 operating incline
 Apron conveyor rollers: 4" diameter
 (10.2 cm) (8)

Screen Drum

Diameter: 5' (1.5 m)
 Length: 11' (3.4 m)

Fines Conveyor

Conveyor belt width: 36" (91.4 cm)
 Conveyor belt type: 220 lb (99.8 kg), 2-ply, 3/16" x
 1/16" (4.8 mm x 1.6 mm)
 Conveyor belt stacking height: 13' (4 m)

Overs Conveyor

Max variable overs belt speed: 144 fpm (43.9 m/min)
 Conveyor belt width: 36" (91.4 cm) wide with raised
 crescent
 Conveyor belt type: 220 lb (99.8 kg), 2-ply, 3/16" x
 1/16" (4.8 mm x 1.6 mm)
 Conveyor belt stacking height: 3' – 10' (.9 m – 3 m)

*Production rates will vary with moisture content,
 maintenance, operator experience, site preparation
 among other factors.*

For a complete list of specifications, visit vermeer.com.



TR516

Built for optimal screening efficiency, the TR516 by Wildcat is an outstanding performer for composting, recycling or topsoil reclamation. The TR516 boasts a 66-hp (49.2 kW) engine, along with a 5'-diameter (1.5 m) drum and 5 cu yd (3.8 m³) hopper. Combine these with .5" (1.3 cm) screens and material moisture content below 40 percent, and the TR516 can produce up to 100 cu yd (76.5 m³) of material per hour.

As with our other units, the TR516 features the largest hopper in its class, standard idlers and tensioned screens for added strength, user-friendly controls, and shielding for minimal spillage.



Our exclusive tensioned-screen panels — manufactured by Wildcat, and available on all trommel screen line models — add strength to the panel and accommodates the installation of smaller-diameter wire when the material allows. This increases production capacity and minimizes sticking, enabling wetter material to be processed.



TR516 Specifications

General Dimensions

Weight: 33,980 lb (15,413.1 kg)
Hitch weight: 15,800 lb (7,166.8 kg)
(weights will vary with options)
Length (transport): 38' (11.6 m)
Width (transport): 102" (259.1 cm)
Height (transport): 13.4' (4.1 m)
Length (operational): 78.3' (23.9 m)
Width (operational): 102" (259.1 cm)
Height (operational): 15.9' (4.9 m)

Capacity

100 cu yd (76.5 m³) per hr with .5" (1.3 cm) screens installed and material with moisture less than 40%

Engine

Make and model: John Deere PE 4024T Tier 3
Cylinders: 4
Engine rating: 66 hp (49.2 kW) @ 2800 rpm 163 ft-lb (221 Nm) of torque @ 1600 rpm
Fuel consumption: 2.4 gph (9.1 L/h) under most operating conditions

Hopper and Apron Conveyor

Hopper capacity: 5 cu yd (3.8 m³)
Hopper height: 9.5' (2.9 m) from ground level at operating incline
Apron conveyor rollers: 6" diameter (15.2 cm) (13)

Screen Drum

Diameter: 5' (1.5 m)
Length: 15' (4.6 m)

Fines Conveyor

Conveyor belt width: 36" (91.4 cm)
Conveyor belt type: 220 lb (99.8 kg), 2-ply, 3/16" x 1/16" (4.8 mm x 1.6 mm)
Conveyor belt stacking height: 14.5' (4.4 m) with drum at 4°

Overs Conveyor

Max variable overs belt speed: 111 fpm (33.8 m/min)
Conveyor belt width: 36" (91.4 cm) wide with raised crescent
Conveyor belt type: 220 lb (99.8 kg), 2-ply, 3/16" x 1/16" (4.8 mm x 1.6 mm)
Conveyor belt stacking height: 3' – 11' (.9 m – 3.4 m)

Production rates will vary with moisture content, maintenance, operator experience, site preparation among other factors.

For a complete list of specifications, visit vermeer.com.

TR516TX

If your organic or wood-waste recycling takes you into hard-to-reach areas or onto uneven terrain, then the TR516TX by Wildcat is the trommel screen for you. Its self-propelled, remote-controlled, tracked undercarriage allows the TR516TX to work hard and productively virtually anywhere.

The TR516TX features a 79-hp (58.9 kW) engine, 5'-diameter (1.5 m) drum and a 5-cu-yd (3.8 m³) hopper — the largest hopper in its class. Complete with its conveyors for fines and overs, the TR516TX can produce up to 100 cu yd (76.5 m³) of material per hour. As with our other units, the TR516TX features removable side panels for easy access, maintenance and cleaning.

TR516TX Specifications

General Dimensions

Weight: 50,000 lb (22,679.7 kg)
 Length (transport): 38' (11.6 m)
 Width (transport): 102" (259.1 cm)
 Height (transport): 12.6' (3.8 m)
 Length (operational): 78.3' (23.9 m)
 Width (operational): 102" (259.1 cm)
 Height (operational): 15.1' (4.6 m)

Capacity

100 cu yd (76.5 m³) per hr with .5" (1.3 cm) screens
 installed and material with moisture less than 40%

Engine

Make and model: John Deere 5030HF Tier 3
 Cylinders: 5
 Engine rating: 99 hp (73.8 kW) @ 2800 rpm 253 ft-lb
 (353 Nm) of torque @ 1400 rpm
 Fuel consumption: 2.8 gph (10.6 L/h) under most
 operating conditions

Hopper and Apron Conveyor

Hopper capacity: 5 cu yd (3.8 m³)
 Hopper height: 9.5' (2.9 m) from ground level at
 operating incline
 Apron conveyor rollers: 6" diameter
 (15.2 cm) (13)

Screen Drum

Diameter: 5' (1.5 m)
 Length: 15' (4.6 m)

Fines Conveyor

Conveyor belt width: 36" (91.4 cm)
 Conveyor belt type: 220 lb (99.8 kg), 2-ply, 3/16" x
 1/16" (4.8 mm x 1.6 mm)
 Conveyor belt stacking height: 15.5' (4.7 m) with drum
 at 4°

Overs Conveyor

Conveyor belt width: 36" (91.4 cm) wide with raised
 crescent
 Conveyor belt type: 220 lb (99.8 kg), 2-ply, 3/16" x
 1/16" (4.8 mm x 1.6 mm)
 Conveyor belt stacking height: 3' – 10' (.9 m – 3 m)

*Production rates will vary with moisture content,
 maintenance, operator experience, site preparation among
 other factors.*

For a complete list of specifications, visit vermeer.com.



TR521

The TR521 by Wildcat trommel screen is specifically designed for topsoil with high moisture content, processing wet material with consistent results. Combine this with its 99-hp (73.8 kW) engine, 5'-diameter (1.5 m) drum and a 5-cu-yd (3.8 m³) hopper, and the TR521 is capable of producing up to 150 cu yd (114.7 m³) of consistent, quality material per hour.

As with our other units, the TR521 features a tall, wide throat opening to help move material smoothly without bridging. Closely set, heavy-duty rollers support the apron conveyor to extend belt life even under tough loading conditions.



TR521 Specifications

General Dimensions

Weight: 39,700 lb (18,007.6 kg)
Hitch weight: 13,400 lb (6078.1 kg)
(weights will vary with options)
Length (transport): 46.1' (14.1 m)
Width (transport): 102" (259.1 cm)
Height (transport): 13.4' (4.1 m)
Length (operational): 84.4' (25.7 m)
Width (operational): 102" (259.1 cm)
Height (operational): 15.9' (4.9 m)

Capacity

150 cu yd (114.7 m³) per hr with .5" (1.3 cm) screens
installed and material with moisture less than 40%

Engine

Make and model: John Deere 5030HF Tier 3
Cylinders: 5
Engine rating: 99 hp (73.8 kW) @ 2800 rpm 253 ft-lb
(353 Nm) of torque @ 1400 rpm
Fuel consumption: 2.8 gph (10.6 L/h) under most
operating conditions

Hopper and Apron Conveyor

Hopper capacity: 5 cu yd (3.8 m³)
Hopper height: 9.5' (2.9 m) from ground level at
operating incline
Apron conveyor rollers: 6" diameter
(15.2 cm) (13)

Screen Drum

Diameter: 5' (1.5 m)
Length: 21' (6.4 m)

Fines Conveyor

Conveyor belt width: 36" (91.4 cm)
Conveyor belt type: 220 lb (99.8 kg), 2-ply, 3/16" x
1/16" (4.8 mm x 1.6 mm)
Conveyor belt stacking height: 14.5' (4.4 m) with drum
at 4°

Overs Conveyor

Max variable overs belt speed: 111 fpm (33.8 m/min)
Conveyor belt width: 36" (91.4 cm) wide with raised
crescent
Conveyor belt type: 220 lb (99.8 kg), 2-ply, 3/16" x
1/16" (4.8 mm x 1.6 mm)
Conveyor belt stacking height: 3' – 10' (.9 m – 3 m)

*Production rates will vary with moisture content,
maintenance, operator experience, site preparation
among other factors.*

For a complete list of specifications, visit vermeer.com.

TR626

The TR626 by Wildcat is the largest screening plant in the trommel screen line. With its 6'-diameter (1.8 m) drum, 7.5-cu-yd (5.7 m³) hopper and 125-hp (93.2 kW) engine, the TR626 can generate up to 200 cu yd (152.9 m³) of material per hour.

Loading and processing organic and wood waste is quicker and more efficient, thanks to the unit's low hopper infeed height and large throat opening. The impressive 72.5'-long (22.1 m) optional radial fines conveyor can rotate 200 degrees to allow you to stockpile large amounts of material without moving the unit. As with our other machines, the TR626 features user-friendly controls and removable side panels for easy access, maintenance and cleaning.



TR626 Specifications

General Dimensions

Weight: 49,700 lb (22,543.5 kg)
Hitch weight: 16,680 lb (7565.9 kg)
(weights will vary with options)
Length (transport): 9.4' (2.9 m)
Width (transport): 105" (266.7 cm)
Height (transport): 13.4' high (4.1 m)
Length (operational): 84.4' (25.7 m)
Width (operational): 105" (266.7 cm)
Height (operational): 15.9' (4.9 m)

Capacity

200 cu yd (152.9 m³) per hr with .5" (1.3 cm) screens installed and material with moisture less than 40%

Engine

Make and model: John Deere 4045H Tier 3
Cylinders: 4
Engine rating: 125 hp (93.2 kW) @ 2400 rpm, 355 ft-lb (481.3 Nm) of torque @ 1500 rpm
Fuel consumption: 3.5 gph (13.2 L/h) under most operating conditions

Hopper and Apron Conveyor

Hopper capacity: 7.5 cu yd (5.4 m³)
Hopper height: 9.5' (2.9 m) from ground level at operating incline
Apron conveyor rollers: 4" diameter (10.2 cm) (14)

Screen Drum

Diameter: 6' (1.8 m)
Length: 26' (7.9 m)

Fines Conveyor

Conveyor belt width: 36" (91.4 cm)
Conveyor belt type: 220 lb (99.8 kg), 2-ply, 3/16" x 1/16" (4.8 mm x 1.6 mm)
Conveyor belt stacking height: 16.6' (5.1 m) with drum at 4°

Overs Conveyor

Max variable overs belt speed: 144 fpm (43.9 m/min)
Conveyor belt width: 48" (121.9 cm) wide with raised crescent
Conveyor belt type: 220 lb (99.8 kg), 2-ply, 3/16" x 1/16" (4.8 mm x 1.6 mm)
Conveyor belt stacking height: 3' – 10' (.9 m – 3 m)

Production rates will vary with moisture content, maintenance, operator experience, site preparation among other factors.

For a complete list of specifications, visit vermeer.com.

Vermeer backs every product with industry-leading service and support.



When you need service, you can count on your local Vermeer dealer. With multiple locations, your Vermeer dealer offers reliable service that helps keep your equipment running.



Whether you need new parts or replacements, when you use Vermeer you can be sure you're getting top quality. That's because all of our parts are designed and manufactured to original Vermeer specifications for maximum performance and durability.

For more information or to schedule a demonstration, contact your local independent, authorized Vermeer dealer today.



Vermeer Corporation
1210 Vermeer Road East
P.O. Box 200
Pella, IA 50219 USA
Phone: +1 (641) 628-3141
Fax: +1 (641) 621-7773
1-888-VERMEER
www.vermeer.com

Vermeer EMEA
(Europe, Middle East, Africa and CIS)
P.O. Box 323
4460 AS Goes
the Netherlands
Phone: +31 113 272700
Fax: +31 113 272727

Vermeer Asia Pacific
48 Toh Guan Road East
#01-105 Enterprise Hub
Singapore 608586
Phone: +65 6516 9560
Fax: +65 6515 9218

Vermeer Latin America
Estrada Duilio Beltrami, 6975
Chacaras Sao Bento - 13278-078
Valinhos, SP - Brazil
Phone: +55-19-3881-3848
Fax: +55-19-3881-3848 Ext. 108

Equipment shown is for illustrative purposes only and may display optional accessories or components. Please contact your local Vermeer dealer for more information about machine specifications.

Vermeer Corporation reserves the right to make changes in engineering, design and specifications; add improvements; or discontinue manufacturing at any time without notice or obligation.

Wildcat Mfg. Co., Incorporated reserves the right to make changes in engineering, design and specifications; add improvements; or discontinue manufacturing at any time without notice or obligation.

Caterpillar is a trademark of Caterpillar, Inc. John Deere is a trademark of Deere and Company. Vermeer and the Vermeer logo are trademarks of Vermeer Manufacturing Company in the United States and/or other countries. Wildcat is a trademark of Wildcat Mfg. Co., Incorporated.

© 2012 Vermeer Corporation. All Rights Reserved